



SPECIFICATIONS

ITEMS		MODELS	CP-27EVS
SPINDLE CAPACITY	With jaw chucks 三爪四爪夾頭		127mm (5")
	With expanding collets 脹開式彈簧套爪		76mm (3")
	With round 5C collets 圓形 5C 套筒夾頭		27mm (1-1/16")
	With Hexagon 5C collets 六邊形 5C 套筒夾頭		22mm (7/8")
	With square 5C collets 正方形 5C 套筒夾頭		19mm(3/4")
	With step chuck 階梯彈簧夾頭		27~152mm (1-1/16" to 6")
Spindle nose diameter 主軸鼻端直徑			φ55.5mm (φ2.189")
Spindle nose I.D/O.D 主軸鼻端 I.D/O.D			5C(10°) / 4° Taper
Variable spindle speeds 主軸轉速(變頻式)			50~4,000 rpm
Inverter spindle motor 變頻主軸馬達			1 HP
Hole through spindle 主軸孔徑			31.75 mm(1-1/4")
Bar stock diameter (5C collet) 棒料直徑(5C 套筒夾頭)			Φ27mm (φ1-1/16")
Swing over bed 床台上旋徑			229 mm (9.016")
Compound slide travel 複式刀座滑動行程			Optional: X:114 mm Y:140 mm
Coolant pump 冷卻泵			optional

Main motor 主軸馬達	3 HP, 220V, 3PH(standard/標準配備)
Net/Gross weight 淨/毛重	660/820 lb. (300 / 370 kg.)
Machine packing dimension 包裝尺寸	1,030 × 970 × 1,670 mm (74" × 34" × 73")

- Specifications are subject to change without notice for further design improvements.